

In the Claims

1. (currently amended) A method for switching active calls between entities on a network device, the method comprising:

determining that a first processor requires maintenance;

collecting information about a current call on the first processor while the current call is being processed by a first entity;

initializing a second processor residing in the network device with the first processor with the information while the current call is being processed on the first processor;

switching the current call from the first processor to the second processor;

releasing the first processor from further processing of the call; and

repeating the switching of the current call from the first processor until the first processor is free from all active calls for maintenance.

2. (previously presented) The method of claim 1 wherein the processors are digital signal processors located within the same module.

3. (previously presented) The method of claim 1 wherein the processors are located in different modules located on the same card.

4. (previously presented) The method of claim 1 wherein the processors are located on different cards in the network device.

5. (previously presented) The method of claim 1 wherein the method further comprises:
copying compression dictionary tables from the first entity; and
loading compression tables in a second entity.

6. (previously presented) The method of claim 1 wherein initializing a second entity further comprises initiating a retrain sequence on the second entity.

7. (original) The method of claim 1 wherein the information about a current call includes modulation.
8. (original) The method of claim 1 wherein the information about a current call includes country code.
9. (previously presented) A computer-readable medium, having contained therein software code that when executed results in:
- identifying a first processor in a network device requiring maintenance;
 - collection of information about a current call on the first processor while the current call is being processed by the first processor;
 - initialization of a second processor in the network device with the information while the current call is still active on the first processor;
 - switching of the current call from the first processor to a second processor;
 - direction of the second processor to retrain and accept the current call; and
 - repeating until the first processor is free of current calls.
10. (previously presented) The computer-readable medium of claim 9, wherein said medium further comprises a downloadable file.
11. (previously presented) The computer-readable medium of claim 9, wherein said medium further comprises an image file uploadable into a digital signal processor.
12. (currently amended) A network device, comprising:
- at least two processing entities residing in the network device, each able to handle at least one active call;
 - a connector operable to connect incoming phone lines to the at least two processing entities; and

a controller to:

determine that a first processor requires maintenance; and

switch each active calls from one entity to another without interruption, ~~thereby eliminating- and to repeatedly switch any~~ active calls on the first entity ~~to free the~~ until the processor is free for maintenance.

13. (previously presented) The device of claim 12 wherein the controller is part of a processor located on one of the entities.

14. (currently amended) A network device, comprising:

at least two means for handling active calls residing in the network device;

a means for connecting the means for handling active calls with means for transmitting phone calls;

a means for determining that a first processing means requires maintenance; and

a means for switching each active calls from a first processing means for handling active calls to another processing means for handling active calls without interruption, ~~thereby eliminating-any- and for repeatedly switching~~ active calls on the first means for handling active calls and ~~freeing-~~ until the first processing means is free for maintenance.

15. (original) The device of claim 14 wherein the device further comprises a modem ISDN channel aggregation device.

16. (original) The device of claim 14 wherein the means for handling active calls further comprises digital signal processors.

17. (original) The device of claim 14 wherein the means for handling active calls further comprise modules located on the same card.

18. (original) The device of claim 14 wherein the means for handling active calls further comprises cards.

19. (original) The device of claim 14 wherein the means for switching active calls further comprises a controller.